

SCHEDA TECNICA – DATA SHEET - DATENBLATT – FICHE TECHNIQUE

Articolo/Article/Artikel/Article	PINEL
Altezza/Width/Breite/Largeur	140 cm
Composizione/Composition/Zusammensetzung/Composition	100%LI
Peso/Weight/Gewicht/Poids	665 gr/m ² – 950 gr/lm
Prodotta in/Made in/Hergestellt in/Fabriqué en	Italia/Italy/Italien/Italie
Tariffa doganale/Custom tariff/Zolltarif/Tarif douaniere	53091900
Resistenza all'abrasione/Abrasion resistance/Scheuerfestigkeit/Résistance à l'abrasion (UNI EN ISO 12947-2 / Martindale)	40.000 rubs
Pilling (5.000 cicli)/Pilling (5.000 rubs)/Pilling (5.000 scheuertouren)/Pilling (5.000 tours) (UNI EN ISO 12945-2)	4
Solidità del colore alla luce/Lightfastness/Lichtechtheit/Solidité à la lumière (UNI EN ISO 105 B02 / Xenotest)	4/5
Solidità del colore allo sfregamento/Fastness to rubbing/Reibechtheit / Solidité au frottement (UNI EN ISO 105 X12)	secco/dry/trocken/sec 4 umido/wet/nass/humide 3/4
Resistenza alla cucitura/Seam slippage/Nahtschiebewidertand/Glisement à la couture (UNI EN ISO 13936)	pass
Resistenza alla lacerazione/Tear strength/Weiterreissfestigkeit/Force de déchirure (UNI EN ISO 13937)	pass
Restringimento/Shrinkage/Schrumpfung/Rétrécissement (trama/ordito)(warp/weft)(schuss/kette)(trame/chaîne)	+ / - 2-3%

**NORME MANUTENZIONE/CARE INSTRUCTIONS
PFLEGEBEHANDLUNG/INSTRUCTIONS D'ENTRETIEN****FIRE RETARDANCY**

Cigarette test	(EN 1021-1) (BS 5852 ign. 0)	
Match test	(EN 1021-2) (BS 5852 ign. 1)	
Classe 1IM	(UNI 9175/1987)	
Crib 5	(BS 5867-2 Type B)	
California	(California Technical Bulletin 117 – Section 1)	pass