

SCHEDA TECNICA – DATA SHEET - DATENBLATT – FICHE TECHNIQUE

Articolo/Article/Artikel/Article	ROSYTA
Altezza/Width/Breite/Largeur	140 cm
Composizione/Composition/Zusammensetzung/Composition	100% PL
Peso/Weight/Gewicht/Poids	310 gr/m ² – 430 gr/lm
Prodotta in/Made in/Hergestellt in/Fabriqué en	Turkey
Tariffa doganale/Custom tariff/Zolltarif/Tarif douaniere	58013700
Resistenza all'abrasione/Abrasion resistance/Scheuerfestigkeit/Résistance à l'abrasion (UNI EN ISO 12947-2 / Martindale)	50.000 rubs
Pilling (5.000 cicli)/Pilling (5.000 rubs)/Pilling (5.000 scheuertouren)/Pilling (5.000 tours) (UNI EN ISO 12945-2)	5
Solidità del colore alla luce/Lightfastness/Lichtechtheit/Solidité à la lumière (UNI EN ISO 105 B02 / Xenotest)	4/5
Solidità del colore allo sfregamento/Fastness to rubbing/Reibechtheit / Solidité au frottement (UNI EN ISO 105 X12)	secco/dry/trocken/sec 4/5 umido/wet/nass/humide 4
Resistenza alla cucitura/Seam slippage/Nahtschiebewidertand/Glissement à la couture (UNI EN ISO 13936)	pass
Resistenza alla lacerazione/Tear strenght/Weiterreissfestigkeit/Force de déchirure (UNI EN ISO 13937)	pass
Restringimento/Shrinkage/Schrumpfung/Rétrécissement (trama/ordito)(warp/weft)(schuss/kette)(trame/chaîne)	+ / - 2-3%

**NORME MANUTENZIONE/CARE INSTRUCTIONS
PFLEGEBEHANDLUNG/INSTRUCTIONS D'ENTRETIEN**