




## SCHEMA TECNICA – DATA SHEET - DATENBLATT – FICHE TECHNIQUE

|   |  |
|---|--|
| Articolo/Article/Artikel/Article  | CARPAZI 930  |
| Altezza/Width/Breite/Largeur  | 140 cm   |
| Composizione/Composition/Zusammensetzung/Composition  | 70% WO – 20% PL – 5% PA – 5% PC                      |
| Peso/Weight/Gewicht/Poids   | 335 gr/m <sup>2</sup> – 490 gr/lm                    |
| Prodotta in/Made in/Hergestellt in/Fabriqué en  | Italia/Italy/Italien/Italie                          |
| Tariffa doganale/Custom tariff/Zolltarif/Tarif douaniere  | 51113080   |
| Resistenza all'abrasione/Abrasion resistance/Scheuerfestigkeit/Résistance à l'abrasion<br>(UNI EN ISO 12947-2 / Martindale) | > 100.000 rubs                                       |
| Pilling (5.000 cicli)/Pilling (5.000 rubs)/Pilling (5.000 scheuertouren)/Pilling (5.000 tours)<br>(UNI EN ISO 12945-2)      | 3/4  |
| Solidità del colore alla luce/Lightfastness/Lichtechtheit/Solidité à la lumière<br>(UNI EN ISO 105 B02 / Xenotest)          | 5  |
| Solidità del colore allo sfregamento/Fastness to rubbing/Reibechtheit / Solidité au frottement<br>(UNI EN ISO 105 X12)      | secco/dry/trocken/sec 4/5<br>umido/wet/nass/humide 4 |
| Resistenza alla cucitura/Seam slippage/Nahtschiebewidertand/Glissement à la couture<br>(UNI EN ISO 13936)                   | pass   |
| Resistenza alla lacerazione/Tear strenght/Weiterreissfestigkeit/Force de déchirure<br>(UNI EN ISO 13937)                    | pass   |
| Shrinkage to dry cleaning<br>(warp and weft)  | + / - 2%   |

NORME MANUTENZIONE/CARE INSTRUCTIONS  
PFLEGEBEHANDLUNG/INSTRUCTIONS D'ENTRETIEN

## FIRE RETARDANCY

|                |                              |      |
|----------------|------------------------------|------|
| Cigarette test | (EN 1021-1) (BS 5852 ign. 0) | pass |
| Match test     | (EN 1021-2) (BS 5852 ign. 1) | pass |