

**SCHEDA TECNICA – DATA SHEET - DATENBLATT – FICHE TECHNIQUE**

Articolo/Article/Artikel/Article	BIEL 100
Altezza/Width/Breite/Largeur	150 cm
Composizione/Composition/Zusammensetzung/Composition	51% Recycled WO – 22% WV 14% PL – 10% PA – 3% PC
Peso/Weight/Gewicht/Poids	435g/sqm – 630g/lm
Prodotta in/Made in/Hergestellt in/Fabriqué en	Italia/Italy/Italien/Italie
Tariffa doganale/Custom tariff/Zolltarif/Tarif douaniere	51113080
Resistenza all'abrasione/Abrasion resistance/Scheuerfestigkeit/Résistance à l'abrasion (UNI EN ISO 12947-2 / Martindale)	> 40.000 rubs
Pilling (5.000 cicli)/Pilling (5.000 rubs)Pilling (5.000 scheuertouren)/Pilling (5.000 tours) (UNI EN ISO 12945-2)	3/4
Solidità del colore alla luce/Lightfastness/Lichtechtheit/Solidité à la lumière (UNI EN ISO 105 B02 / Xenotest)	5
Solidità del colore allo sfregamento/Fastness to rubbing/Reibechtheit / Solidité au frottement (UNI EN ISO 105 X12)	secco/dry/trocken/sec 4/5 umido/wet/nass/humide 4
Resistenza alla cucitura/Seam slippage/Nahtschiebewidertand/Glisement à la couture (UNI EN ISO 13936)	pass
Resistenza alla lacerazione/Tear strength/Weiterreissfestigkeit/Force de déchirure (UNI EN ISO 13937)	pass
Restringimento/Shrinkage/Schrumpfung/Rétrécissement (trama/ordito)(warp and weft)(schuss/kette)(trame/chaîne)	+/- 2%

**NORME MANUTENZIONE/CARE INSTRUCTIONS  
PFLEGEBEHANDLUNG/INSTRUCTIONS D'ENTRETIEN****FIRE RETARDANCY**

Cigarette test	(EN 1021-1) (BS 5852 ign. 0)	pass
Match test	(EN 1021-2) (BS 5852 ign. 1)	pass